

References

- [1] J. A. Lee and M. Verleysen. *Nonlinear dimensionality reduction*. Springer Science & Business Media, 2007.
- [2] J. A. Lee, A. Lendasse, and M. Verleysen. Nonlinear projection with curvilinear distances: Isomap versus curvilinear distance analysis. *Neurocomputing*, 57:49–76, 2004.
- [3] J. A. Lee and M. Verleysen. Shift-invariant similarities circumvent distance concentration in stochastic neighbor embedding and variants. *Proc. Computer Science*, 4:538–547, 2011.
- [4] G. Hinton and S. Roweis. Stochastic neighbor embedding. In *NIPS*, volume 15, pages 833–840, 2002.
- [5] J. Venna, J. Peltonen, K. Nybo, H. Aidos, and S. Kaski. Information retrieval perspective to nonlinear dimensionality reduction for data visualization. *Journal of Machine Learning Research*, 11(Feb):451–490, 2010.
- [6] J. A. Lee, E. Renard, G. Bernard, P. Dupont, and M. Verleysen. Type 1 and 2 mixtures of Kullback-Leibler divergences as cost functions in dimensionality reduction based on similarity preservation. *Neurocomputing*, 112:92–108, 2013.
- [7] J. A. Lee, D. H. Peluffo-Ordóñez, and M. Verleysen. Multi-scale similarities in stochastic neighbour embedding: Reducing dimensionality while preserving both local and global structure. *Neurocomputing*, 169:246–261, 2015.
- [8] L. van der Maaten and G. Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9(Nov):2579–2605, 2008.
- [9] Z. Yang, J. Peltonen, and S. Kaski. Scalable Optimization of Neighbor Embedding for Visualization. In *ICML (2)*, pages 127–135, 2013.
- [10] L. Van Der Maaten. Accelerating t-SNE using tree-based algorithms. *Journal of Machine Learning Research*, 15(1):3221–3245, 2014.
- [11] J. A. Lee and M. Verleysen. Quality assessment of dimensionality reduction: Rank-based criteria. *Neurocomputing*, 72(7):1431–1443, 2009.
- [12] S. A. Nene, S. K. Nayar, and H. Murase. Columbia object image library (COIL-20), 1996.
- [13] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.
- [14] M. Lichman. UCI Machine Learning Repository. <http://archive.ics.uci.edu/ml>, 2013. University of California, Irvine, School of Information and Computer Sciences.
- [15] M. A. Little, P. E. McSharry, S. J. Roberts, D. A.E. Costello, and I. M. Moroz. Exploiting nonlinear recurrence and fractal scaling properties for voice disorder detection. *BioMedical Engineering OnLine*, 6(1):23, 2007.
- [16] I-C. Yeh. Modeling slump flow of concrete using second-order regressions and artificial neural networks. *Cement and Concrete Composites*, 29(6):474–480, 2007.
- [17] D Gil, JL Girela, J De Juan, MJ Gomez-Torres, and M Johnsson. Predicting seminal quality with artificial intelligence methods. *EXPERT SYST APPL*, 39(16):12564–12573, 2012.
- [18] R. Bhatt. Planning-Relax Dataset for Automatic Classification of EEG Signals'. UCI.
- [19] PFB Silva, ARS Marcal, and RMA da Silva. Evaluation of features for leaf discrimination. *Lecture Notes in Computer Science*, 7950:197–204, 2013. Springer.
- [20] N. Abreu. Analise do perfil do cliente Recheio e desenvolvimento de um sistema promocional. ISCTE-IUL, Lisbon, 2011. Mestrado em Marketing.
- [21] O. Akbilgic, H. Bozdogan, and M. E. Balaban. A novel Hybrid RBF Neural Networks model as a forecaster. *Statistics and Computing*, 24(3):365–375, 2014.
- [22] HT Kahraman, S Sagiroglu, and I Colak. The development of intuitive knowledge classifier and the modeling of domain dependent data. *KNOWL-BASED SYST*, 37:283–295, 2013.
- [23] I-C. Yeh. Modeling of strength of high-performance concrete using artificial neural networks. *Cement and Concrete research*, 28(12):1797–1808, 1998.
- [24] G. Zoutendijk. *Methods of feasible directions: a study in linear and non-linear programming*. Elsevier, 1960.